



According to 1907/2006/EG, Article 31

Revision: 03.05.2016

Version number 2

Page 1 of 8

Printing date: 17.04.2019

Profisep 2010

1. Identification of the substance / Preparation and Company:

- 1.1 Identification of the substance or preparation:
Commercial product name: Profisep 2010
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:
No further relevant information available.
Application of the substance / the mixture: Separating fluid
- 1.3 Manufacturer/Supplier: ERNST HINRICHS Dental GmbH
Street / mailbox: Borsigstr. 1
Country code. / postal code / city: D - 38644 Goslar
Phone: 0 53 21 / 5 06 24
Fax: 0 53 21 / 5 08 81
E-mail / Website: info@hinrichs-dental.de / www.hinrichs-dental.de
Further information obtainable from: ERNST HINRICHS Dental GmbH
- 1.4 Emergency telephone number
ERNST HINRICHS Dental GmbH: +49 (0) 53 21 / 5 06 24 - 25 (Mon-Fri. 8 a.m. – 4 p.m.)

2. Hazards Identification:

- 2.1 Classification of the substance or mixture
Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.
Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

- 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08 GHS09

Signal word: Hazard
Hazard-determining components of labelling: Heptane
Propan-2-ol

Hazard statements
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.



Profisep 2010

H336	May cause drowsiness or dizziness.
H304	May be fatal if swallowed and enters airways.
H410	Very toxic to aquatic life with long lasting effects.
Precautionary statements	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing mist/vapours/spray.
P280	Wear protective gloves / eye protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.
P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- 2.3 Other hazards:
 Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

3. Composition / Information on Ingredients:

3.2 Chemical characterization:	Mixture.	
Description:	Mixture of substances listed below with non-hazardous additions.	
Dangerous components:		
CAS: 67-63-0	Propan-2-ol	25-50 %
EINECS: 200-661-7	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 142-82-5	Heptane	10-25 %
EINECS: 205-563-8	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 108-87-2	Methylcyclohexane	2,5-10 %
EINECS: 203-624-3	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 110-82-7	Cyclohexane	2,5-10 %
EINECS: 203-806-2	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	

Additional information: For the wording of the listed risk phrases refer to section 16.

4. First aid measures:

- | | |
|--------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| 4.1 After inhalation: | In case of unconsciousness place patient stably in side position for transportation. Supply fresh air; consult doctor in case of complaints. |
| 4.2 After skin contact: | Immediately wash with water and soap and rinse thoroughly. |
| 4.3 After eye contact: | Rinse open eye for several minutes under running water. If symptoms persist, consult a doctor. |
| 4.4 After swallowing: | Do not induce vomiting; call for medical help immediately. |
| 4.5 Most important symptoms and effects, both acute and delayed: | No further relevant information available. |
| 4.6 Indication of any immediate medical attention and special treatment needed | No further relevant information available. |

5. Fire Fighting measures:

- | | |
|------------------------------------|---------------------------------------------------------------------------------------------------------|
| 5.1 Suitable extinguishing agents: | CO ₂ , powder or water spray. Fight larger fires with water spray or alcohol resistant foam. |
|------------------------------------|---------------------------------------------------------------------------------------------------------|



According to 1907/2006/EG, Article 31

Revision: 03.05.2016

Version number 2

Profisep 2010

- | | |
|--------------------------------------------------------------|--------------------------------------------|
| For safety reasons unsuitable extinguishing agents: | Full water jet. |
| 5.2 Special hazards arising from the substance or mixture | No further relevant information available. |
| 5.3 Advice for firefighters
Special protective equipment: | No special measures required. |

6. Accidental release measures:

- | | |
|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 6.1 Person-related safety precautions: | Wear protective equipment. Keep unprotected persons away. |
| 6.2 Measures for environmental protection: | In case of penetration into waters or the sewage system, inform the competent authorities.
Do not allow to enter the sewage system/surface water/groundwater. |
| 6.3 Measures for cleaning / collecting: | Absorb with liquid-binding material (sand, diatomite, universal binders and sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation. |
| 6.4 Reference to other sections: | See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information. |

7. Handling and Storage:

- | | |
|------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7.1 Handling:
Precautions for safe handling: | Store in cool and dry place in tightly closed containers.
Notes on fire and explosion protection:
Keep sources of ignition away - no smoking.
Take measures against electrostatic charging. |
| 7.2 Conditions for safe storage, including any incompatibilities
Storage: | Requirements for storage rooms and containers: store in a cool place.
Information on common storage: not required.
Further information on storage conditions:
Keep containers tightly closed.
Store in cool and dry place in tightly closed containers.
Storage class: SC 3 |
| 7.3 Further information about storage conditions:
Specific end use(s) | Keep container tightly sealed.
Store in cool, dry conditions in well-sealed receptacles.
No further relevant information available. |

8. Exposure controls / Personal protection:

- | | |
|-----------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Additional information on the design of technical systems: | No further information, see Section 7. |
| 8.1 Ingredients with limit values that require monitoring at the workplace: | |
| 67-63-0 propan-2-ol | OEL - long-term value: 500 mg/m ³ , 200 ml/m ³ / 2(II); DFG, Y |
| 142-82-5 heptane | TLV - long-term value: 2100 mg/m ³ , 500 ml/m ³ |
| 108-87-2 Methylcyclohexane | OEL - long-term value: 810 mg/m ³ , 200 ml/m ³ / 2(II); DFG |
| 110-82-7 cyclohexane | OEL - long-term value: 700 mg/m ³ , 200 ml/m ³ / 4(II); DFG, EU |



According to 1907/2006/EG, Article 31

Revision: 03.05.2016

Version number 2

Page 4 of 8

Printing date: 17.04.2019

Profisep 2010

Components with biological limit values:

67-63-0 Propan-2-ol

BLV 25 mg/l

Sample material: Whole blood

Sampling time: end of exposure or shift

Parameter: Acetone

25 mg/l

Sample material: Urine

Sampling time: end of exposure or shift

Parameter: Acetone

110-82-7 Cyclohexane

BLV 150 mg/g creatinine

Sample material: Urine

Sampling time: for long-term exposure: after several previous shifts, end of exposure or end of shift

Parameter: 1,2-Cyclohexandiol (after hydrolysis)

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:
General protective and hygienic measures:

Keep away from food, drink and animal feed.
Take off contaminated, soaked clothing immediately.
Wash hands prior to breaks and at the end of work.
Avoid contact with eyes and skin.

Respiratory protection:

Not required with good room ventilation.

Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product / the substance / the preparation. Due to missing tests, no recommendation to the glove material can be given for the product / the preparation / the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves:

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Gloves made of the following materials are suitable for permanent contact:

Polychloroprene - CR (0.5 mm): breakthrough time > 4 h
Nitrile rubber/nitrile latex - NBR (0.35 mm): breakthrough time > 4h
Butyl rubber - butyl (0.5 mm): breakthrough time > 8 h
Fluorinated rubber - FKM (0.4 mm): breakthrough time > 8 h
Polyvinylchloride - PVC (0.5 mm): breakthrough time > 4 h
This recommendation is based exclusively on the chemical compatibility and the test according to EN 374 under laboratory conditions.

Depending on the use, different requirements may arise.

Therefore, the recommendations of the supplier of the protective gloves must also be taken into account.

Nitrile rubber.

Gloves made of the following materials are suitable as splash protection:

Eye protection:

Tightly sealed safety goggles.

9. Physical and chemical properties:

9.1 General information:

Appearance:

Form:

liquid



According to 1907/2006/EG, Article 31

Revision: 03.05.2016

Version number 2

Profisep 2010

Colour:	Clear
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
9.2 Change in condition:	
Boiling point / Boiling range:	78°C
Flash point:	-9°C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	215°C
Decomposition temperature:	Not determined.
Self-igniting:	Product is not self-igniting.
Danger of explosion:	The product is not explosive, however, the formation of explosive vapour/air mixtures is possible.
Explosion limits:	
Lower:	1,1 Vol %
Upper:	12,0 Vol %
Vapour pressure at 20 °C:	48 hPa
Density at 20°C:	0,74 g/cm ³
Relative density:	Not determined.
Vapour density:	Not determined.
Evaporation rate:	Not determined.
Solubility in / miscibility with water:	Not miscible or hardly miscible.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	70,0 %
Water:	0 %
VOC (EC):	78 %
9.2 Other information:	No further relevant information available.

10. Stability and Reactivity:

10.1	Reactivity	
10.2	Chemical stability	
	Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
10.2	Possibility of hazardous reactions:	No hazardous reactions known.
10.3	Conditions to avoid:	No further relevant information available.
10.4	Incompatible materials:	No further relevant information available.
10.5	Hazardous decomposition products:	No hazardous decomposition products known.

11. Toxicological Information:

11.1	Information on toxicological effects
	Acute toxicity:
	Classification-relevant LD/LC50 values:
	67-63-0 propan-2-ol
	Oral / LD50 / 5045 mg/kg (rat)
	Dermal / LD50 / 12800 mg/kg (rabbit)
	Inhalative / LC50 / 4 h 30 mg/l (rat)
	108-87-2 methylcyclohexane
	Oral / LD50 / 2250 mg/kg (mouse)
	110-82-7 cyclohexane
	Oral LD50 12705 mg/kg (rat)

Primary irritant effect:



According to 1907/2006/EG, Article 31

Revision: 03.05.2016

Version number 2

Page 6 of 8

Printing date: 17.04.2019

Profisep 2010

- Etching/irritant effect on the skin: Irritating to skin and mucous membranes.
- Severe eye damage/irritation Irritant effect.
- Sensitisation of the respiratory tract/skin No sensitising effect known.

Additional toxicological information:

Based on the calculation method of the General Classification Guideline

of the EU for preparations in the last amended version, the product exhibits the following hazards:

- Irritant
- Sensitisation not applicable
- CMR effects (carcinogenic, mutagenic and teratogenic)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity at single exposure: Based on available data, the classification criteria are not met.

Specific target organ toxicity at repeated exposure: Based on available data, the classification criteria are not met.

12. Ecological Information:

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability: No further relevant information available.
- 12.3 Bioaccumulative potential: No further relevant information available.
- 12.4 Mobility in soil: No further relevant information available.
- Ecotoxicological effects:
- Note: Very toxic for fish.
- Further ecological information:
- General notes: Water hazard class: 2 (self-classification): hazardous to water
Do not allow to enter groundwater, waters or the sewage system.
Also toxic to fish and plankton in waters.
very toxic to aquatic life
- 12.5 Results of PBT and vPvB assessment:
- PBT: Not applicable.
- vPvB: Not applicable.

13. Disposal Considerations:

- 13.1 Waste treatment methods
- Recommendation: Must not be disposed of together with household waste.
Do not allow to enter the sewage system.
- European waste catalogue:
- 07 00 00 WASTES FROM ORGANIC CHEMICAL PROCESSES
- 07 07 00 Wastes from the MFSU of fine chemicals and chemical products
not otherwise specified.
- 07 07 04* Other organic solvents, washing liquids and mother liquors
- Uncleaned packaging –
Recommendation: Disposal in accordance with official regulations.

14. Transport Information:

- 14.1 UN-Number UN1993
- ADR, IMDG, IATA:
- 14.2 UN proper shipping name 1993 FLA MM ABLE L IQU ID , N. O. S. (HEPTANE,
ADR: ISOPROPANOL (ISOPROPYLALCOHOL))
- IMDG, IATA: FLAMMABLE LIQUID, N.O.S. (HEPTANES, ISOPROPANOL
(ISOPROPYL ALCOHOL))
- 14.3 Transport hazard class:
- ADR:



According to 1907/2006/EG, Article 31

Revision: 03.05.2016

Version number 2

Profisep 2010



Class: 3 Flammable liquid substances.
 Hazard label: 3
 IMDG, IATA



Class: 3 Flammable liquids.
 Label: 3
 ADR, IMDG, IATA

14.4 Packaging group:

ADR, IMDG, IATA: II

14.5 Environmental hazards:

Marine pollutant: No.

Special marking (ADR): Symbol (fish and tree)

14.6 Special precautions for user

Caution; Flammable liquid substances

Kemler number: 33

EMS number: F-E,S-E

14.7 Transport in bulk according to Annex II of the MARPOL Agreement and according to the IBC Code:

Transport/Additional information:

ADR

Excepted quantities (EQ): E2

Limited quantity (LQ): 1L

Transport category: 2

Tunnel restriction code: D/E

Comments: Limited quantity: maximum 30 kg per package, apply "diamond with black corners" label to the transport package.

UN „Model Regulation“: UN1993, FLAMMABLE LIQUID SUBSTANCE, N.A.G. (HEPTANE, ISOPROPANOL (ISOPROPYLALCOHOL)), ENVIRONMENTALLY HAZARDOUS, 3, II

15. Regulatory Information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to Regulation (EC) 1272/2008 GHS labelling elements

National regulations:

Ordinance on Major Accidents: The quantity thresholds according to the Ordinance on Major Accidents must be observed.

Water hazard class: WGK 2 (self-classification): hazardous to water.

Other regulations, restrictions and prohibition ordinances

Customs tariff number: 3403 99 00

15.2 Chemical safety assessment: A chemical safety assessment has not been conducted.

16. Further Information:

The information is based on the current state of our knowledge, however, it does not represent a guarantee of product characteristics and does not establish a contractual legal relationship.

16.1 Relevant sentences:

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.



According to 1907/2006/EG, Article 31

Revision: 03.05.2016

Version number 2

Page 8 of 8

Printing date: 17.04.2019

Profisep 2010

H400	Very toxic to aquatic life.
H410	Toxic to aquatic life with long lasting effects.
H411	Very toxic to aquatic life with long lasting effects.

16.2 Abbreviations and acronyms:

RID:	Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail).
IATA:	International Air Transport Association.
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the “International Civil Aviation Organization”.
ADR:	Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road).
IMDG:	International Maritime Code for Dangerous Goods.
IATA:	International Air Transport Association
GHS:	Globally Harmonized System of Classification and Labelling of Chemicals.
EINECS:	European Inventory of Existing Commercial Chemical Substances
ELINCS:	European List of Notified Chemical Substances
CAS:	Chemical Abstracts Service (division of the American Chemical Society)
LC50:	Lethal concentration, 50 percent.
LD50:	Lethal dose, 50 percent.
Flam. Liq. 2:	Flammable liquids, Hazard Category 2
Skin Irrit. 2:	Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2:	Serious eye damage/eye irritation, Hazard Category 2
STOT SE 3:	Specific target organ toxicity - Single exposure, Hazard Category 3
Asp. Tox. 1:	Aspiration hazard, Hazard Category 1
Aquatic Acute 1:	Hazardous to the aquatic environment - Acute Hazard, Category 1
Aquatic Chronic 1:	Hazardous to the aquatic environment - Chronic Hazard, Category 1
Aquatic Chronic 2:	Hazardous to the aquatic environment - Chronic Hazard, Category 2

* Data changed versus the previous version